

**ELECTRONIC DEVICE INCLUDING FINGERPRINT SENSOR
AND DISPLAY HAVING SELECTABLE MENU ITEMS AND
ASSOCIATED METHODS**

Field of the Invention

[0001] The present invention relates to the field of personal identification and, more particularly, to the field of fingerprint sensing and processing.

Background of the Invention

[0002] Fingerprint sensing and matching is a reliable and widely used technique for personal identification or verification. In particular, a common approach to fingerprint identification involves scanning a sample fingerprint or an image thereof and storing the image and/or unique characteristics of the fingerprint image. The characteristics of a sample fingerprint may be compared to information for reference fingerprints already in a database to determine proper identification of a person, such as for verification purposes. AuthenTec, Inc., of Melbourne, FL, offers a number of particularly advantageous fingerprint sensors under the designation numbers AF-S2, AFS5800, AES4000, AES3400, and AES2500, for example. These integrated circuit fingerprint sensors are also described in U.S. Patent Nos. 5,963,679 and 6,259,804, for example, and operate based upon electric field sensing and have proven to be very accurate, as well as reliable.

[0003] Electronic devices sometimes use menus so that a user may select a menu item from among a plurality of menu items on the menu. More

particularly, the menu items may be arranged in a column format so that the user may scroll up or down to select one of the menu items. Other electronic devices include menu items arranged in a plurality of columns so that a user may scroll up, down, or sideways to select a particular menu item. Typically, however, valuable real estate on the housing of the electronic device may be necessary to enable these scrolling and selecting features. In other words, scrolling and selecting features may require multiple switches on the housing.

[0004] Some electronic devices use fingerprint sensing applications, as well as a menu scrolling/selection application to allow a user to select a menu item from among a plurality of menu items. These electronic devices, however, may be larger and somewhat bulky due to excess sensing areas and buttons necessary to perform fingerprint sensing, scrolling through a plurality of menu items, and selection of a menu item.

[0005] An electronic device disclosed in published U.S. Patent Application Publication No. 2001/0017934 to Paloniemi et al. attempts to account for this problem by providing a sensing data input. The electronic device includes a fingerprint sensor and movement detector that is responsive to movement of the user's skin over the sensor. In other words, the movement detector is responsive to swiping movement of the user's finger over the fingerprint sensor. A fingerprint distortion problem, however, may exist with this type of sensor. Accordingly, the fingerprint sensor may not be able to properly read the user's moving fingerprint, causing delays or errors in selecting a menu item.

[0006] Moving finger detection may also require higher power consumption than is desirable by the sensor and by the associated processor that may be internal or external to the sensor. Moving finger

gestures may also not be practical in situations where the sensor is mounted in close proximity to other devices, restricting finger motion. The sliding finger motions required by moving finger detection systems may not be easily performed on hand-held devices designed for one-handed operation, such as a cell phone operated by the thumb.

[0007] Movement detectors may also be disadvantageous due to excessive power consumption. Further, a movement detector that is responsive to movement of a user's finger may be impractical in situations where the motion detector is mounted in close proximity to other devices. In other words, the finger motion may cause inadvertent activation of other devices in close proximity to the motion detector.

Summary of the Invention

[0008] In view of the foregoing background, it is therefore an object of the present invention to provide an electronic device having a fingerprint sensor for accurately sensing a fingerprint, and which sensor is compact, rugged, and also allows a user to scroll an indicator among a plurality of menu items.

[0009] This and other objects, features, and advantages of the present invention are provided by an electronic device comprising a housing, a display carried by the housing, and a fingerprint sensor, also carried by the housing. The electronic device may further comprise a processor for generating a plurality of menu items on the display, and for scrolling an indicator along the menu items based upon static placement of a finger adjacent a selected portion of the fingerprint sensor. Scrolling the indicator along the menu items based upon static placement is advantageously reliable, may use lower power, and may only require recognition of a lower quality image than is typically needed to detect motion of a finger.

[0010] The fingerprint sensor may comprise a fingerprint sensing area having a polygonal shape defining a plurality of spaced apart corner portions. The processor may scroll the indicator in a direction corresponding to a pointing direction of a respective corner portion upon which the user's finger is placed. In some embodiments, the polygonal shape of the fingerprint sensing area may be a diamond shape, for example.

[0011] In a first class of embodiments of the electronic device, the plurality of menu items may be arranged in a single column. In these embodiments, the plurality of spaced apart corner portions may be defined by an upper corner portion for scrolling the indicator in an upward direction portion through the menu items, and a downward corner for scrolling the indicator in a downward direction through the menu items. In addition, a first-side corner portion may be for selecting a menu item, and a second-side corner portion may be for returning to a previous menu.

[0012] In a second class of embodiments of the electronic device, the plurality of menu items may be arranged in a plurality of columns. In these embodiments, the plurality of spaced apart corner portions may be defined by an upper corner portion for scrolling the indicator in an upward direction, and a downward corner portion for scrolling the indicator in a downward direction. In addition, a first-side corner portion may be for scrolling the indicator in a direction towards a first side of the display, and a second-side corner for scrolling the indicator in a direction towards a second side of the display.

[0013] The processor may also cooperate with the fingerprint sensor to first verify an identity of a user based upon sensing a fingerprint prior to permitting scrolling. The electronic device may further comprise a memory for storing at least one authorized fingerprint. More specifically, the

processor may verify the fingerprint of the user by comparing the fingerprint of the user to the authorized fingerprint stored in the memory. The processor may enable scrolling within a predetermined time window of verifying the identity of the user.

[0014] In some embodiments, the processor may be switchable to a lower power operating mode when a user's finger is not sensed on said fingerprint sensor. The fingerprint sensor may comprise a plurality of fingerprint sensing elements, and the process may determine static placement based upon a pattern of fingerprint sensing elements less than a full number of fingerprint sensing elements. In some embodiments, the electronic device may comprise logic circuitry between the processor and the sensing elements.

[0015] The plurality of menu items may comprise at least one further menu, which may include a different plurality of menu items. In some embodiments, the plurality of menu items may comprise a back item and a forward item. Accordingly, a user may readily move back and forth between selected menu items. In other embodiments, the processor may select a menu item marked with the indicator based upon a tapping of the fingerprint sensing area. Tapping may be determined based upon simultaneously detecting placement of the finger on a plurality of corner portions. In other words, if two or more corner portions are covered, a selection is determined.

[0016] The housing may comprise a handheld housing, and the electronic device may also include a power supply carried by the housing and connected to the display, fingerprint sensor, and processor. The electronic device may include circuitry connected to the processor so that the electronic device comprises a portable telephone, a pager, or a personal digital assistant (PDA), for example.

[0017] A method aspect of the present invention is for indicating a menu item from among a plurality of

menu items on a display of an electronic device. The method may comprise scrolling an indicator along the menu items based upon static placement of a finger adjacent a selected portion of the fingerprint sensor.

Brief Description of the Drawings

[0018] FIG. 1 is a schematic block diagram of a first embodiment of an electronic device according to the present invention.

[0019] FIG. 2 is a schematic block diagram of a sequence of displayed menus of the electronic device shown in FIG. 1.

[0020] FIG. 3 is a schematic diagram illustrating fingerprint sensing elements on the fingerprint sensor of the electronic device shown in FIG. 1.

[0021] FIG. 4 is a schematic block diagram of a second embodiment of an electronic device according to the present invention.

[0022] FIG. 5 is a flow chart illustrating a first embodiment of a method for indicating and selecting a menu item according to the present invention.

[0023] FIG. 6 is a flow chart illustrating a second embodiment of a method for indicating and selecting a menu item according to the present invention.

Detailed Description of the Preferred Embodiments

[0024] The present invention will now be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. Like numbers refer to like elements throughout, and prime notation is used to indicate similar elements in alternate embodiments.

[0025] Referring initially to FIG. 1, a first embodiment of an electronic device **20** is now described. The electronic device **20** illustratively comprises a housing **22**, and a display **24** carried by the housing. The housing **22** may, in some embodiments, be a handheld housing. The display **24** may be a liquid crystal display, for example, or any other kind of display as will be appreciated by those skilled in the art. The electronic device **20** further illustratively comprises a fingerprint sensor **30** that may also be carried by the housing **22**. The fingerprint sensor **30** may be similar to those disclosed in U.S. Patent Nos. 5,963,679 and 6,259,804, assigned to the assignee of the present invention, the entire disclosures of which are incorporated herein by reference.

[0026] The electronic device **20** also illustratively includes a processor **40** for generating a plurality of menu items **45a-45d** on the display **24**. The processor **40** also scrolls an indicator **42** along the menu items **45a-45d** based upon static placement of a user's finger adjacent a selected portion of the fingerprint sensor **30**. The indicator **42** in the illustrated embodiment highlights the menu item **45a-45d** to be selected by inverting the color of the menu item, e.g., menu item #2 **45b**. The indicator **42** may also be a different colored block, a pointer, for example, or any other type of indicator as understood by those skilled in the art.

[0027] Scrolling the indicator **42** through the menu items **45a-45d** based upon static placement of a finger over the fingerprint sensor **30** is particularly advantageous and more reliable than other methods of scrolling through menu items. For example, other prior art approaches of scrolling are based on methods include swiping a finger over a fingerprint sensor to scroll through menu items, which may be unreliable, as some sensors tend not to pick up the swiping motion of the user's finger. Scrolling the indicator **42** through

the menu items **45a-45d** based upon static placement of a user's finger over the fingerprint sensor **30**, however, may be more accurate and faster than these other approaches. This is also advantageous in that the electronic device **20** may be operated using one hand. Further, by scrolling the indicator **42** based upon static placement of a user's finger, other devices on the electronic device **20** are not interfered with. In other words, a user is less likely to inadvertently depress another button on the electronic device **20** when scrolling the indicator through the menu items **45a-45d**.

[0028] In some embodiments, the electronic device **20** may be switched to a lower power operating mode. More specifically, the electronic device **20** may switch to the lower power operating mode when a user's finger is not present on the fingerprint sensor **30**. When in the lower power operating mode, the electronic device **20** advantageously consumes less power to thereby allow longer operating time before the need to recharge or replace a power source. The electronic device **20** may simply detect when a user's finger is present on the fingerprint sensor **30** to thereby exit the lower power operating mode.

[0029] The fingerprint sensor **30** illustratively includes a fingerprint sensing area **32** having a polygonal shape defining a plurality of spaced apart corner portions **35a-35d**. In one embodiment of the electronic device **20**, the processor **40** scrolls the indicator **42** in a direction corresponding to a pointing direction of a respective corner portion **35a, 35b**. The polygonal shape of the fingerprint sensing area **32** is illustratively a diamond, but may be any other shape, as understood by those skilled in the art.

[0030] The menu items **45a-45d** are illustratively arranged in a single column. The plurality of spaced apart corner portions are illustratively defined by an upper corner portion **35a** for scrolling the indicator **42** in an upward direction through the menu items **45a-45d**,

and a downward corner portion **35b** for scrolling the indicator in a downward direction through the menu items. A first-side corner portion **35c** is for selecting a menu item, and a second side-corner portion **35d** is for returning to a previous menu. More specifically, static placement of the user's finger on the first-side corner portion **35c** will select the menu item that is highlighted by the indicator **42**, e.g., menu item #2 **45b**.

[0031] The processor **40** may cooperate with the fingerprint sensor **30** to first verify an identity of a user based upon sensing a fingerprint prior to permitting scrolling through the menu items **45a-45d**. Indeed, sensing authorized fingerprints may be desired before displaying the menu as will be appreciated by those skilled in the art. In other embodiments, the fingerprint may be read during selective placement of the finger of the user on a corner portion although less of the overall fingerprint may be available in these embodiments.

[0032] To verify the identity of the user, the electronic device **20** illustratively comprises a memory **50** for storing at least one authorized fingerprint. The memory **50** may be embedded within the processor **40** in other embodiments. The processor **40** verifies the fingerprint of the user by comparing the fingerprint sensed on the fingerprint sensor **30** to the authorized fingerprint stored in the memory **50**. More specifically, the electronic device **20** may be switched to a learning mode so that certain characteristics of authorized fingerprints may be stored into the memory **50**. When in learning mode, authorized fingerprints may be added and deleted from the memory **50** of the electronic device **20**, as will be appreciated by those skilled in the art.

[0033] As a security measure, the processor **40** may enable scrolling within a predetermined time window of verifying the identity of the user. In other words, if

the user does not scroll through the menu items **45a-45d** within the predetermined time window, the processor **40** may return to a start-up display image or otherwise lock the user out so that the user may not use the fingerprint sensor **30** to scroll through and/or select the menu items. Similarly, if the processor **40** senses inactivity for a predetermined time, it may also lock out the user. Inactivity may indicate that the user has completed use of the electronic device **20** and has merely set it down. Accordingly, the processor **40** may automatically lock the electronic device **20** so that an unauthorized user may not scroll through and/or select menu items **45a-45d**.

[0034] Referring additionally to FIG. 2, the process of selection of menu items **45a-45d** is now further described. The plurality of menu items **45a-45d** may comprise at least one further menu, which may include a different plurality of menu items **47a-47d**. For example, upon selection of menu item #2 **45b**, another menu may appear on the display **24** having another plurality of menu items **47a-47d**. Accordingly, a user may select from these menu items **47a-47d**, which may bring the user to another set of menu items, or may go back to the previous menu items **45a-45d** as will be understood by those skilled in the art. Again, an indicator **42** may be provided by inverting the color of the menu item, as illustrated by menu item #2a **47a**.

[0035] The electronic device **20** also illustratively comprises a power supply in the form of a battery **52** carried by the housing **22** and connected to the display **24**, fingerprint sensor **30**, and processor **40**. The electronic device **20** also illustratively comprises other device circuitry **60** connected to the processor **40**. Accordingly, the electronic device may include the respective additional circuitry to be a portable telephone **62**, a laptop computer **64**, a pager **66**, or a personal digital assistant (PDA) **68**, for example. Of course, other circuitry may be included so that the

electronic device **20** may comprise any type of device, as shall be understood by those skilled in the art.

[0036] The present invention may include various implementations of logic to detect finger position. Referring more specifically to FIG. 3, the fingerprint sensor **30** may comprise a plurality of pixels, or fingerprint sensing elements **30a-30d**. As will be appreciated by those skilled in the art, the pixels' size is greatly exaggerated for clarity of explanation. More particularly, the fingerprint sensor **30** may detect a user's fingerprint by scanning only a selected set of pixels. Scanning only a selected set of fingerprint sensing elements **30a-30d**, rather than an entire array, may reduce power consumption, and may advantageously increase frame rate and responsiveness of the fingerprint sensor **30**. In the illustrated embodiment, each of the corners **35a-35d** of the fingerprint sensor **30** may include respective fingerprint sensing elements **30a-30d**, which may be scanned to detect finger position. A number of other scan patterns may be used that have specific sensitivities to different aspects of the finger placement, as understood by those skilled in the art.

[0037] Given a scanned pattern, determining the position of the finger may be performed by software running on the processor **40**, or, since no complex ridge patterns need to be manipulated, it may be performed in onboard logic **57**. On-chip implementations may be faster than software and may use significantly less power to perform the tracking operation. In other terms, the fingerprint sensor **30** may comprise a plurality of fingerprint sensing elements. Further, the electronic device **20** illustratively includes onboard logic **57** between the sensing elements **30a-30d** and the processor **40**. The onboard logic **57**, may determine static placement based upon a pattern of fingerprint sensing elements less than a full number of fingerprint sensing elements.

[0038] Turning now additionally to FIG. 4, a second embodiment of the electronic device **20'** is now described. In the second embodiment, the menu items **45a'-45f'** are illustratively arranged in a pair of columns. Although a pair of columns are illustrated, those skilled in the art will appreciate that any number of columns may be provided. Further, the plurality of spaced apart corner portions are defined by an upper corner portion **35a'** for scrolling the indicator **42'** in an upward direction through the menu items **45a'-45f'**, and a downward corner portion **35b'** for scrolling the indicator in a downward direction through the menu items. A first-side or right-side corner portion **35c'** is for scrolling the indicator towards a first side of the display **24'**, and a second-side or left-side corner portion **35d'** is for scrolling the indicator towards a second side of the display. Accordingly, static contact by a finger over a desired corner portion (leaving the other corner portion uncovered) causes scrolling in the direction of the contacted corner portion.

[0039] The plurality of menu items may also comprise a back item **45e'** and a forward item **45f'**. More particularly, the back item **45e'** may be selected when the user wishes to scroll through menu items on a previous menu, and the forward item **45f'** may be selected when the user wishes to scroll through menu items on a subsequent menu. The processor **40'** may select the menu item **45a'-45f'** marked with the indicator **42'** based upon a tapping of the fingerprint sensing area **32'**. Of course, other contact with the fingerprint sensing area **32'** may also be used to select the menu item **45a'-45f'** marked with the indicator **42'**. The other elements of the second embodiment of the electronic device **20'** are similar to those of the first embodiment, are marked with prime notation, and require no further discussion herein.

[0040] Turning now additionally to the flow chart **70** of FIG. 5, a method of indicating and selecting a menu item from among a plurality of menu items **45a-45d** on a display **42** of an electronic device **20** is now described. From the start (Block **72**), a user's fingerprint is sensed on the fingerprint sensor **30** at Block **74**. At Block **76**, it is determined whether the sensed fingerprint is an authorized fingerprint. If it is determined at Block **76** that the sensed fingerprint is an authorized fingerprint, then the user is allowed to scroll to a menu item in a column of menu items **45a-45d** by sensing finger placement on an upper or lower corner portion of the fingerprint sensor **30** at Block **80**. If, however, it is determined at Block **76** that the sensed fingerprint is not an authorized fingerprint, then the user is not allowed to scroll through or select menu items **45a-45d** at Block **78**.

[0041] At Block **82**, a menu item is selected from among the plurality of menu items **45a-45d** by placing a finger of the user on a first-side corner portion **35c** of the fingerprint sensor **30**. At Block **84**, the user may go back to a previous menu by placing a finger on a second-side corner portion **35d** of the fingerprint sensor **30**.

[0042] At Block **86**, it is determined whether a predetermined time of inactivity has elapsed after an authorized fingerprint was sensed. If it is determined at Block **86** that the predetermined time has elapsed, then the user is not allowed to continue. If, however, it is determined at Block **86** that the predetermined time has not elapsed, then the user is allowed to scroll through and select other menu items **45a-45d** at Blocks **80** and **82**.

[0043] Turning now additionally to the flow chart **100** of FIG. 6, a second embodiment of the method of indicating and selecting a menu item from among a plurality of menu items **45a'-45f'** on a display **42'** of an electronic device **20'** is now described. From the

start (Block **102**), a user's fingerprint is sensed on the fingerprint sensor **30'** at Block **104**. At Block **106**, it is determined whether the sensed fingerprint is an authorized fingerprint. If it is determined at Block **106** that the sensed fingerprint is an authorized fingerprint, then the user is allowed to scroll to a menu item **45a'-45f'** by sensing finger placement on respective corner portions of the fingerprint sensor **30** at Block **110**. If, however, it is determined at Block **106** that the sensed fingerprint is not an authorized fingerprint, then the user is not allowed to scroll through or select menu items **45a'-45f'** at Block **108**.

[0044] At Block **112**, a menu item from among a plurality of menu items **45a'-45f'** is selected by tapping a finger on the fingerprint sensing area **32'**. By tapping, a user's finger will be placed upon a plurality of corner portions. Based upon detection of placement of the finger on the two or more corner portions, the user's selection is determined by the processor. At Block **114**, the user may go back to a previous menu by selecting a back menu item **35e'**.

[0045] At Block **116**, it is determined whether a predetermined time of inactivity has elapsed after an authorized fingerprint was sensed. If it is determined at Block **116** that the predetermined time has elapsed, then the user is not allowed to continue. If, however, it is determined at Block **116** that the predetermined time has not elapsed, then the user is allowed to scroll through and select other menu items **45a'-45f'** at Blocks **110** and **112**.

[0046] Many modifications and other embodiments of the invention will come to the mind of one skilled in the art having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is to be understood that the invention is not to be limited to the specific embodiments disclosed, and that modifications and

embodiments are intended to be included within the scope of the appended claims.